

Patton SmartNode 5531 - Telnet - HTTP - TFTP - HTTP - HTTPS - 10,100,1000 Mbit/s - IEEE 802.1Q, IEEE 802.1p - 961 g - 190,5 x 260,35 x 95,25 mm - 10 W



4 BRI - 8 VoIP Calls - 4 SIP Sessions (SIP b2b UA) upgradeable
 (max. 200) - 4 Transcoded SIP Sessions - SIP-TLS - SRTP - High
 Precision 5ppm Clock - 2x Gig Ethernet - 1x USB port - external UI
 power (100–240 VAC) NA/EU

Gruppe	Zubehör Telefone
Hersteller	Patton
Hersteller Art. Nr.	SN5531/4BIS8VHP/EUI
EAN/UPC	0847840012950

Hauptmerkmale

	Allgemein
Management-Protokolle	Telnet, HTTP, TFTP, HTTP, HTTPS
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s
Netzstandard	IEEE 802.1Q, IEEE 802.1p
Gewicht	961 g
Abmessungen (BxTxH)	190,5 x 260,4 x 95,2 mm
Stromverbrauch (Standardbetrieb)	10 W
Eingangsspannung	100 - 240 V
Sicherheit	EN60950, TBR-3
Zertifizierung	FCC Part 15, CE RTTE 99/5/EC