

Patton SmartNode 5531 - Telnet - HTTP -  
 TFTP - HTTP - HTTPS - 10,100,1000 Mbit/s  
 - IEEE 802.1Q, IEEE 802.1p - 961 g - 190,5 x  
 260,35 x 95,25 mm - 10 W



4 BRI - 8 VoIP Calls - 4 SIP Sessions (SIP b2b UA) upgradeable (max.  
 200) - 4 Transcoded SIP Sessions - SIP-TLS - SRTP - High Precision  
 5ppm Clock - 2x Gig Ethernet - 1x USB port - external UI power (100-  
 240 VAC) NA/EU

|                     |                     |
|---------------------|---------------------|
| Gruppe              | Zubehör Telefone    |
| Hersteller          | Patton              |
| Hersteller Art. Nr. | SN5531/4BIS8VHP/EUI |
| EAN/UPC             | 0847840012950       |

## Hauptmerkmale

### Allgemein

|                                     |                                 |
|-------------------------------------|---------------------------------|
| Management-Protokolle               | Telnet, HTTP, TFTP, HTTP, HTTPS |
| Ethernet LAN Datentransferraten     | 10,100,1000 Mbit/s              |
| Netzstandard                        | IEEE 802.1Q, IEEE 802.1p        |
| Gewicht                             | 961 g                           |
| Abmessungen (BxTxH)                 | 190,5 x 260,4 x 95,2 mm         |
| Stromverbrauch<br>(Standardbetrieb) | 10 W                            |
| Eingangsspannung                    | 100 - 240 V                     |
| Sicherheit                          | EN60950, TBR-3                  |
| Zertifizierung                      | FCC Part 15, CE RTTE 99/5/EC    |