

Patton SmartNode 4131 - G.168 - G.711Mu
 - G.722 - G.722.2 - G.723.1 - G.726 - G.729 -
 G.729A - G.729ab - T.38 - EN 60950 - TBR-3
 - FCC Part 15 - CE - Telnet - TFTP - HTTP -
 HTTPS - SNMPv3 - 100-240 V



8 BRI TE/NT - 16 VoIP Calls - 4 SIP-SIP Calls (SIP b2b UA) upgradeable
 (max. 200) - Optional SIP-TLS - SRTP - 1x Gig Ethernet - 1x USB port -
 High Precision 5ppm Clock - external UI power (100-240 VAC) NA/EU

Gruppe	Netzwerkgeräte
Hersteller	Patton
Hersteller Art. Nr.	SN4131/8BIS16VHP/EUI
EAN/UPC	0847840011632

Hauptmerkmale

Allgemein

Sprachcodec	G.168, G.711Mu, G.722, G.722.2, G.723.1, G.726, G.729, G.729A, G.729ab
Telefaxkompatibilität	T.38
Sicherheit	EN 60950, TBR-3
Management-Protokolle	Telnet, TFTP, HTTP, HTTPS, SNMPv3
AC Eingangsspannung	100-240 V
Stromverbrauch (Standardbetrieb)	10 W
Abmessungen (BxTxH)	374,6 x 260,4 x 95,2 mm
Gewicht	1,24 kg