

Patton SmartNode 5531 - Telnet - HTTP -
 TFTP - HTTP - HTTPS - 10,100,1000 Mbit/s
 - IEEE 802.1Q, IEEE 802.1p - 1,24 kg - 374,6
 x 260,35 x 95,25 mm - 10 W



8 BRI - 16 VoIP Calls - 4 SIP-SIP Calls (SIP b2b UA) upgradeable (max.
 200) - 4 Transcoded Calls - SIP-TLS - SRTP - High Precision 5ppm Clock
 - 3x Gig Ethernet - 1x USB port - external UI power (100-240 VAC)
 NA/EU

Gruppe	Zubehör Telefone
Hersteller	Patton
Hersteller Art. Nr.	SN5531/8BIS16VHP/EUI
EAN/UPC	0847840011625

Hauptmerkmale

Allgemein

Sicherheit	EN60950, TBR-3
Zertifizierung	FCC Part 15, CE RTTE 99/5/EC
Sprachcodec	G.168, G.711Mu, G.722, G.722.2, G.723.1, G.726, G.729, iLBC
Management-Protokolle	Telnet, HTTP, TFTP, HTTP, HTTPS
Ethernet LAN Datentransferraten	10,100,1000 Mbit/s
Netzstandard	IEEE 802.1Q, IEEE 802.1p
Stromverbrauch (Standardbetrieb)	10 W
Eingangsspannung	100 - 240 V