

Patton SmartNode 5531 - Telnet - HTTP -
 TFTP - HTTP - HTTPS - 10,100,1000 Mbit/s
 - IEEE 802.1Q, IEEE 802.1p - 961 g - 190,5 x
 260,35 x 95,25 mm - 10 W



4 BRI - 8 VoIP Calls - 4 SIP Sessions (SIP b2b UA) upgradeable (max.
 200) - 4 Transcoded SIP Sessions - SIP-TLS - SRTP - High Precision
 5ppm Clock - 2x Gig Ethernet - 1x USB port - external UI power (100-
 240 VAC) NA/EU

| | |
|---------------------|---------------------|
| Gruppe | Zubehör Telefone |
| Hersteller | Patton |
| Hersteller Art. Nr. | SN5531/4BIS8VHP/EUI |
| EAN/UPC | 0847840012950 |

Hauptmerkmale

| | Allgemein |
|-------------------------------------|---------------------------------|
| Management-Protokolle | Telnet, HTTP, TFTP, HTTP, HTTPS |
| Ethernet LAN Datentransferraten | 10,100,1000 Mbit/s |
| Netzstandard | IEEE 802.1Q, IEEE 802.1p |
| Gewicht | 961 g |
| Abmessungen (BxTxH) | 190,5 x 260,4 x 95,2 mm |
| Stromverbrauch (Standardbetrieb) | 10 W |
| Eingangsspannung | 100 - 240 V |
| Sicherheit | EN60950, TBR-3 |
| Zertifizierung | FCC Part 15, CE RTTE 99/5/EC |